

# MMJT9435

Preferred Device

## Bipolar Power Transistors

### PNP Silicon

#### Features

- Pb-Free Packages are Available
- Collector -Emitter Sustaining Voltage –  
 $V_{CEO(sus)} = 30 \text{ Vdc (Min) @ } I_C = 10 \text{ mAdc}$
- High DC Current Gain –  
 $h_{FE} = 125 \text{ (Min) @ } I_C = 0.8 \text{ Adc}$   
 $= 90 \text{ (Min) @ } I_C = 3.0 \text{ Adc}$
- Low Collector -Emitter Saturation Voltage –  
 $V_{CE(sat)} = 0.275 \text{ Vdc (Max) @ } I_C = 1.2 \text{ Adc}$   
 $= 0.55 \text{ Vdc (Max) @ } I_C = 3.0 \text{ Adc}$
- SOT-223 Surface Mount Packaging
- Epoxy Meets UL 94, V-0 @ 0.125 in
- ESD Ratings: Human Body Model, 3B; > 8000 V  
Machine Model, C; > 400 V



**ON Semiconductor®**


<http://onsemi.com>

#### POWER BJT

**$I_C = 3.0 \text{ AMPERES}$**


**$BV_{CEO} = 30 \text{ VOLTS}$**

**$V_{CE(sat)} = 0.275 \text{ VOLTS}$**




Schematic

#### MARKING DIAGRAM




SOT-223  
CASE 318E  
STYLE 1



9435 = Specific Device Code  
A = Assembly Location  
WW = Work Week

#### PIN ASSIGNMENT



Top View Pinout

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

**Preferred** devices are recommended choices for future use and best overall value.

# MMJT9435

## MAXIMUM RATINGS (T<sub>C</sub> = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V <sub>CEO</sub>	30	Vdc
Collector–Base Voltage	V <sub>CB</sub>	45	Vdc
Emitter–Base Voltage	V <sub>EB</sub>	6.0	Vdc
Base Current – Continuous	I <sub>B</sub>	1.0	Adc
Collector Current – Continuous – Peak	I <sub>C</sub>	3.0 5.0	Adc
Total Power Dissipation @ T <sub>C</sub> = 25°C Derate above 25°C Total P <sub>D</sub> @ T <sub>A</sub> = 25°C mounted on 1" sq. (645 sq. mm) Collector pad on FR–4 bd material Total P <sub>D</sub> @ T <sub>A</sub> = 25°C mounted on 0.012" sq. (7.6 sq. mm) Collector pad on FR–4 bd material	P <sub>D</sub>	3.0 24 1.56 0.72	W mW/°C W
Operating and Storage Junction Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	–55 to +150	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

## THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction–to–Case – Junction–to–Ambient on 1" sq. (645 sq. mm) Collector pad on FR–4 bd material – Junction–to–Ambient on 0.012" sq. (7.6 sq. mm) Collector pad on FR–4 bd material	R <sub>θJC</sub> R <sub>θJA</sub> R <sub>θJA</sub>	42 80 174	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	T <sub>L</sub>	260	°C

## ORDERING INFORMATION

Device	Package	Shipping†
MMJT9435T1	SOT–223	1000 / Tape & Reel
MMJT9435T1G	SOT–223 (Pb–Free)	1000 / Tape & Reel
MMJT9435T3	SOT–223	4000 / Tape & Reel
MMJT9435T3G	SOT–223 (Pb–Free)	4000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MMJT9435

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Collector–Emitter Sustaining Voltage (I <sub>C</sub> = 10 mA, I <sub>B</sub> = 0 A)	V <sub>CEO(sus)</sub>	30	–	–	Vdc
Emitter–Base Voltage (I <sub>E</sub> = 50 μA, I <sub>C</sub> = 0 A)	V <sub>EBO</sub>	6.0	–	–	Vdc
Collector Cutoff Current (V <sub>CE</sub> = 25 Vdc, R <sub>BE</sub> = 200 Ω) (V <sub>CE</sub> = 25 Vdc, R <sub>BE</sub> = 200 Ω, T <sub>J</sub> = 125°C)	I <sub>CER</sub>	–	–	20 200	μA
Emitter Cutoff Current (V <sub>BE</sub> = 5.0 Vdc)	I <sub>EBO</sub>	–	–	10	μA

### ON CHARACTERISTICS (Note 1)

Collector–Emitter Saturation Voltage (I <sub>C</sub> = 0.8 A, I <sub>B</sub> = 20 mA) (I <sub>C</sub> = 1.2 A, I <sub>B</sub> = 20 mA) (I <sub>C</sub> = 3.0 A, I <sub>B</sub> = 0.3 A)	V <sub>CE(sat)</sub>	–	0.155	0.210 0.275 0.550	Vdc
Base–Emitter Saturation Voltage (I <sub>C</sub> = 3.0 A, I <sub>B</sub> = 0.3 A)	V <sub>BE(sat)</sub>	–	–	1.25	Vdc
Base–Emitter On Voltage (I <sub>C</sub> = 1.2 A, V <sub>CE</sub> = 4.0 Vdc)	V <sub>BE(on)</sub>	–	–	1.10	Vdc
DC Current Gain (I <sub>C</sub> = 0.8 A, V <sub>CE</sub> = 1.0 Vdc) (I <sub>C</sub> = 1.2 A, V <sub>CE</sub> = 1.0 Vdc) (I <sub>C</sub> = 3.0 A, V <sub>CE</sub> = 1.0 Vdc)	h <sub>FE</sub>	125 110 90	220	– – –	–

### DYNAMIC CHARACTERISTICS

Output Capacitance (V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0 A, f = 1.0 MHz)	C <sub>ob</sub>	–	100	150	pF
Input Capacitance (V <sub>EB</sub> = 8.0 Vdc)	C <sub>ib</sub>	–	135	–	pF
Current–Gain – Bandwidth Product (Note 2) (I <sub>C</sub> = 500 mA, V <sub>CE</sub> = 10 V, F <sub>test</sub> = 1.0 MHz)	f <sub>T</sub>	–	110	–	MHz

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
2. f<sub>T</sub> = |h<sub>FE</sub>| • f<sub>test</sub>




Figure 1. Collector Saturation Region




Figure 2. Collector Saturation Region

# MMJT9435




Figure 3. DC Current Gain




Figure 4. DC Current Gain




Figure 5. "On" Voltages




Figure 6. "On" Voltages




Figure 7.  $V_{BE(on)}$  Voltage




Figure 8. Output Capacitance

# MMJT9435




Figure 9. Current-Gain Bandwidth Product




Figure 10. Active Region Safe Operating Area




Figure 11. Power Derating

There are two limitations on the power handling ability of a transistor: average junction temperature and secondary breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 10 is based on  $T_{J(pk)} = 150^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. Secondary breakdown pulse limits are valid for duty cycles to 10% provided  $T_{J(pk)} \leq 150^\circ\text{C}$ .  $T_{J(pk)}$  may be calculated from the data in Figure 12. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by secondary breakdown.





Figure 12. Thermal Response

# MMJT9435

## PACKAGE DIMENSIONS

SOT-223 (TO-261)  
CASE 318E-04  
ISSUE K




- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.249	0.263	6.30	6.70
B	0.130	0.145	3.30	3.70
C	0.060	0.068	1.50	1.75
D	0.024	0.035	0.60	0.89
F	0.115	0.126	2.90	3.20
G	0.087	0.094	2.20	2.40
H	0.0008	0.0040	0.020	0.100
J	0.009	0.014	0.24	0.35
K	0.060	0.078	1.50	2.00
L	0.033	0.041	0.85	1.05
M	0°	10°	0°	10°
S	0.264	0.287	6.70	7.30

- STYLE 1:  
PIN 1. BASE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 611312, Phoenix, Arizona 85082-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.

1000 万+元器件 PDF 数据手册在线免费下载: <https://pdf.ttic.cc>

Electronic Component Datasheets Free Download: <https://pdf.ttic.cc>

国内知名度极高的电子元器件行业 B2B 供求平台（1 亿+库存信息，30 万+日访问量，终端工程师及工厂首选平台）：<https://www.ttic.cc>

Highly renowned B2B supply and demand platform for electronic components industry (More than 100,000,000 inventory information, More than 300,000 visits per daily , preferred platform for terminal engineers and factories):  
<https://www.ttic.cc>

全球供应商库存及价格信息: <http://price.hqbdsj.com>

Electronic Component's Price & Stock: <http://price.hqbdsj.com>