

LBTP3100Z4TZHG

S-LBTP3100Z4TZHG

PNP Silicon AF Power Transistors


1. FEATURES

- For AF driver and output stages
- High collector current
- High current gain
- Low collector-emitter saturation voltage
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S-prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.




2. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LBTP3100Z4TZHG	PC	1000/Tape&Reel



3. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector–Emitter Voltage	VCEO	-100	V
Collector–Base Voltage	VCBO	-120	V
Emitter–Base Voltage	VEBO	-7	V
Collector Current — Continuous	IC	-3	A
Peak collector current (tp ≤ 10 ms)	ICM	-5	A
Base current	IB	-200	mA
Peak base current	IBM	-500	mA
Junction and Storage temperature	TJ, Tstg	-55~+150	°C



4. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Total Device Dissipation, FR-4 Board (Note 1) @ TA = 25°C	PD	1	W
Thermal Resistance, Junction–to–Ambient(Note 1)	ROJA	125	°C/W

1. FR-4 = 30.0mm×25.0mm×1.6mm.

5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector–Emitter Breakdown Voltage (IC = -10 mA, IB = 0)	VBR(CEO)	-100	-	-	V
Collector–Base Breakdown Voltage (IC = -100 μA, IE = 0)	VBR(CBO)	-120	-	-	V
Emitter–Base Breakdown Voltage (IE = -10 μA, IC = 0)	VBR(EBO)	-7	-	-	V
Collector Cutoff Current (VCB = -45V, IE = 0) (VCB = -45V, IE = 0, Ta = 150°C)	ICBO	-	-	-0.1 -20	μA
Emitter CutOff Current (VEB = -4 V, IC = 0)	IEBO	-	-	-100	nA

ON CHARACTERISTICS (Note 2)





DC Current Gain (IC = -10mA, VCE = -5V) (IC = -500mA, VCE = -1V) (IC = -1A, VCE = -2V)	HFE	25 85 15	- - -	- 475 -	
Collector–Emitter Saturation Voltage (IC = -2A, IB = -0.2A)	VCE(sat)	-	-	-0.5	V
Base–Emitter Saturation Voltage (IC = -2A, IB = -0.2A)	VBE(sat)	-	-	-1.3	V

SMALL–SIGNAL CHARACTERISTICS




Transitional Frequency (IC = -50 mA, VCE = -10 V, f = 100 MHz)	fT	-	100	-	MHz
Collector-base capacitance (VCB = -10 V, f = 100 MHz)	Ccb	-	40	-	pF

2.Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.

6. ELECTRICAL CHARACTERISTICS CURVES




6. ELECTRICAL CHARACTERISTICS CURVES(Con.)



7. OUTLINE AND DIMENSIONS

SOT223




SOT223			
DIM	MIN	NOR	MAX
A	1.50	1.60	1.70
A1	0.00	0.05	0.10
A2	0.80	0.90	1.00
b1	2.90	3.02	3.10
b2	0.60	0.72	0.80
c	0.20	0.27	0.35
D	6.30	6.50	6.70
E	3.30	3.50	3.70
e	4.60BSC		
e1	2.30BSC		
HE	6.80	7.00	7.20
L	0.80	1.00	1.20
L1	1.75(REF)		
θ	0°~8°		
$\theta 1$	8°	10°	12°
All Dimensions in mm			

GENERAL NOTES

1. Top package surface finish $Ra0.4 \pm 0.2 \mu m$
2. Bottom package surface finish $Ra0.7 \pm 0.2 \mu m$
3. Side package surface finish $Ra0.4 \pm 0.2 \mu m$
4. Protrusion or Gate Burrs shall not exceed 0.10mm per side.

8. SOLDERING FOOTPRINT



SOT223	
DIM	(mm)
X1	3.80
Y1	2.00
X2	1.20
Y2	2.00
C1	2.30
C2	6.30

DISCLAIMER

- Before you use our Products, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.